

↔		↔		⌚		⌒		⌘	⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
38	1 1/2			5	75				0,210	0,140
51	2			5	75				0,270	0,180
63	2 1/2			4	60				0,380	0,255
76	3			4	60				0,530	0,360
102	4			4	60				0,710	0,480
152	6			3	45				1,180	0,795
203	8			3	45				1,800	1,210
NA		LA		NEU		EMEA		SA	AP	AU



286EE

Water discharge - PVC - lay flat - standard duty

Tube: Blue PVC
Reinforcement: High tensile textile cords
Cover: Blue PVC - abrasion and ozone resistant
Use: Lay flat water discharge
Safety factor: 3:1
Temperature: -10 °C +60 °C (+14 °F +140 °F)

↔		↔		⌚		⌒		⌘	⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
25	1			10	150				0,190	0,130
32	1 1/4			9	135				0,240	0,160
38	1 1/2			8	120				0,300	0,200
45	1 3/4			8	120				0,350	0,235
51	2			8	120				0,410	0,275
63	2 1/2			8	120				0,560	0,380
76	3			8	120				0,680	0,460
102	4			7	100				1,000	0,675
152	6			4	60				1,600	1,080
NA		LA		NEU		EMEA		SA	AP	AU



288HH

Water discharge - PVC - lay flat - heavy duty

Tube: Red PVC
Reinforcement: High tensile textile cords
Cover: Red PVC - abrasion and ozone resistant
Use: Lay flat water discharge
Safety factor: 3:1
Temperature: -10 °C +60 °C (+14 °F +140 °F)

↔		↔		⌚		⌒		⌘	⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
102	4	110	4,33	5	75				1,660	1,120
152	6	160	6,30	5	75				2,410	1,620
203	8	213	8,39	5	75				3,230	2,175
254	10	264	10,39	5	75				3,980	2,675
NA		LA		NEU		EMEA		SA	AP	AU



250AA

Water discharge 5 bar (75 psi) - lay flat

Tube: Black EPDM
Reinforcement: High tensile textile cords
Cover: Black EPDM - abrasion and ozone resistant
Use: Lay flat water discharge
Safety factor: ≤ 102 mm 3:1 ≥ 152 mm 2:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		⌚		⌒		⌘	⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
32	1 1/4	40	1,57	10	150				0,460	0,310
38	1 1/2	46	1,81	10	150				0,540	0,365
40	1 9/16	48	1,89	10	150				0,570	0,385
45	1 3/4	53	2,09	10	150				0,660	0,445
51	2	59	2,32	10	150				0,730	0,495
60	2 3/8	68	2,68	10	150				0,860	0,580
63	2 1/2	71	2,80	10	150				0,890	0,600
70	2 3/4	78	3,07	10	150				1,190	0,800
76	3	84	3,31	10	150				1,280	0,865
90	3 1/2	98	3,86	10	150				1,480	0,995
102	4	110	4,33	10	150				1,770	1,190
127	5	137	5,39	10	150				2,400	1,615
152	6	162	6,38	10	150				2,970	2,000
168	6 5/8	178	7,01	10	150				3,220	2,165
203	8	215	8,46	10	150				4,190	2,820
254	10	270	10,63	10	150				7,600	5,110
305	12	319	12,56	10	150				8,810	5,925
NA		LA		NEU		EMEA		SA	AP	AU



253AA

Water discharge 10 bar (150 psi) - lay flat

Tube: Black EPDM
Reinforcement: High tensile textile cords
Cover: Black EPDM - abrasion and ozone resistant
Use: Lay flat water discharge
Safety factor: 3:1 ≥ 203 mm 2:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)