

↔		↔		⌚		⤴		☼		♠	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
19	3/4	33	1,30	10	150				0,710	0,480	
19	3/4	35	1,38	10	150				0,830	0,560	
25	1	39	1,54	10	150				0,870	0,585	
32	1 1/4	48	1,89	10	150				1,240	0,835	
38	1 1/2	55	2,17	10	150				1,650	1,110	
40	1 9/16	60	2,36	10	150				1,930	1,300	
51	2	71	2,80	10	150				2,400	1,615	
19	3/4	38	1,50	10	150				1,000	0,675	
25	1	48	1,89	10	150				1,540	1,035	
32	1 1/4	55	2,17	10	150				1,830	1,230	
38	1 1/2	60	2,36	10	150				2,080	1,400	
51	2	73	2,87	10	150				2,630	1,770	
NA	LA	NEU	EMEA	SA	AP	AU					



65 mm³

750AA Sandblast 10 bar (150 psi)

Tube: Black conductive NR - abrasion resistant
Reinforcement: High tensile textile cords
Cover: Black SBR/NR - abrasion and ozone resistant - pin pricked
Use: Abrasive material blasting
Safety factor: 3:1
Temperature: -40 °C +80 °C (-40 °F +176 °F)

↔		↔		⌚		⤴		☼		♠	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
13	1/2	27	1,06	10	150				0,560	0,380	
19	3/4	33	1,30	10	150				0,710	0,480	
25	1	39	1,54	10	150				0,880	0,595	
32	1 1/4	48	1,89	10	150				1,240	0,835	
38	1 1/2	55	2,17	10	150				1,660	1,120	
51	2	71	2,80	10	150				2,420	1,630	
NA	LA	NEU	EMEA	SA	AP	AU					



65 mm³

750AH Sandblast 10 bar (150 psi)

Tube: Black conductive NR - abrasion resistant
Reinforcement: High tensile textile cords
Cover: Red SBR/EPDM - abrasion and ozone resistant - pin pricked
Use: Abrasive material blasting
Safety factor: 3:1
Temperature: -40 °C +80 °C (-40 °F +176 °F)

↔		↔		⌚		⤴		☼		♠	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
19	3/4	38	1,50	10	150				1,010	0,680	
25	1	48	1,89	10	150				1,540	1,035	
32	1 1/4	55	2,17	10	150				1,840	1,240	
38	1 1/2	60	2,36	10	150				2,090	1,405	
NA	LA	NEU	EMEA	SA	AP	AU					



65 mm³

750AG Sandblast 10 bar (150 psi)

Tube: Black conductive NR - abrasion resistant
Reinforcement: High tensile textile cords
Cover: Green SBR/EPDM - abrasion and ozone resistant - pin pricked
Use: Abrasive material blasting
Safety factor: 3:1
Temperature: -40 °C +80 °C (-40 °F +176 °F)

↔		↔		⌚		⤴		☼		♠	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
13	1/2	27	1,06	10	150				0,500	0,340	
19	3/4	33	1,30	10	150				0,640	0,435	
25	1	39	1,54	10	150				0,790	0,535	
32	1 1/4	48	1,89	10	150				1,140	0,770	
38	1 1/2	55	2,17	10	150				1,490	1,005	
51	2	71	2,80	10	150				2,140	1,440	
25	1	48	1,89	10	150				1,400	0,945	
32	1 1/4	55	2,17	10	150				1,670	1,125	
38	1 1/2	60	2,36	10	150				1,900	1,280	
51	2	73	2,87	10	150				2,410	1,620	
19	3/4	40	1,57	10	150				1,030	0,695	
51	2	76	2,99	10	150				2,650	1,785	
NA	LA	NEU	EMEA	SA	AP	AU					



★
TOP
50 mm³

753AA Sandblast 10 bar (150 psi) premium quality

Tube: Premium black conductive NR - abrasion resistance 50 mm³ (ISO 4649/A)
Reinforcement: High tensile textile cords
Cover: Black SBR/NR - abrasion and ozone resistant - pin pricked
Use: Abrasive material blasting. Designed for long service life in heavy duty applications
Safety factor: 3:1
Temperature: -40 °C +80 °C (-40 °F +176 °F)