

↔		↔		⊕	↷		⊕		⊕		
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
6	1/4	10	0,39	20	300	24	1,00		0,065	0,044	
8	5/16	12	0,47	20	300	32	1,25		0,080	0,055	
10	3/8	15	0,59	20	300	40	1,50		0,110	0,075	
13	1/2	19	0,75	20	300	52	2,00		0,180	0,120	
16	5/8	23	0,91	20	300	64	2,50		0,260	0,175	
19	3/4	26	1,02	20	300	76	3,00		0,300	0,200	
25	1	33	1,30	20	300	100	4,00		0,440	0,300	
NA	LA	NEU	EMEA	SA	AP	AU					



195AT

Compressed air 20 bar (300 psi) - polyurethane pneumatic tools

Tube: Black polyurethane/PVC - oil mist resistant

Reinforcement: High tensile textile cords

Cover: Light blue synthetic elastomer - abrasion and ozone resistant

Use: Compressed air. Specially designed for pneumatic tools and paint spray

Safety factor: 3:1

Temperature: -20 °C +60 °C (-4 °F +140 °F)

↔		↔		⊕	↷		⊕		⊕		
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
10	3/8	16	0,63	20	300	80	3,00		0,170	0,115	
13	1/2	19	0,75	20	300	104	4,00		0,205	0,140	
19	3/4	27	1,06	20	300	152	6,00		0,370	0,250	
25	1	34	1,34	20	300	200	8,00		0,530	0,360	
NA	LA	NEU	EMEA	SA	AP	AU					



191AK

Compressed air 20 bar (300 psi) - PVC exceeds AS/NZS 2554/B

Tube: Black PVC - oil mist resistant

Reinforcement: High tensile textile cords

Cover: Yellow ribbed PVC with longitudinal blue stripes - abrasion and ozone resistant

Use: Compressed air and general industrial applications.

Also suitable for crop spraying of fertilizers, pesticides and weed killers

Safety factor: 3,2:1

Temperature: -5 °C +60 °C (+23 °F +140 °F)