

↔		↔		⌚		⌒		⌘		⚡	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
19	3/4	29	1,14	10	150				0,470	0,320	
25	1	35	1,38	10	150				0,580	0,390	
32	1 1/4	42	1,65	10	150				0,710	0,480	
38	1 1/2	48	1,89	10	150				0,840	0,565	
51	2	61	2,40	10	150				1,110	0,750	
63	2 1/2	75	2,95	10	150				1,630	1,100	
76	3	88	3,46	10	150				1,960	1,320	
102	4	114	4,49	10	150				2,650	1,785	
32	1 1/4	44	1,73	10	150				0,880	0,595	
35	1 3/8	47	1,85	10	150				0,960	0,650	
38	1 1/2	50	1,97	10	150				1,030	0,695	
40	1 9/16	52	2,05	10	150				1,070	0,720	
45	1 3/4	57	2,24	10	150				1,190	0,800	
51	2	63	2,48	10	150				1,350	0,910	
NA	LA	NEU	EMEA	SA	AP	AU					



650AA
Fuel-oil delivery 10 bar (150 psi)

Tube: Black conductive NBR
Reinforcement: High tensile textile cords
Cover: Black conductive CR - abrasion, ozone, hydrocarbon and fire resistant
Use: General purpose fuel and oil delivery
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		⌚		⌒		⌘		⚡	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
38	1 1/2	48	1,89	10	150				0,920	0,620	
51	2	61	2,40	10	150				1,220	0,820	
76	3	88	3,46	10	150				2,120	1,425	
102	4	114	4,49	10	150				2,850	1,920	
19	3/4	29	1,14	10	150				0,520	0,350	
22	7/8	32	1,26	10	150				0,580	0,390	
25	1	35	1,38	10	150				0,650	0,440	
32	1 1/4	44	1,73	10	150				0,960	0,650	
38	1 1/2	50	1,97	10	150				1,140	0,770	
51	2	63	2,48	10	150				1,460	0,985	
63	2 1/2	77	3,03	10	150				2,080	1,400	
76	3	92	3,62	10	150				2,550	1,715	
NA	LA	NEU	EMEA	SA	AP	AU					



650AH
Fuel-oil delivery 10 bar (150 psi)

Tube: Black conductive NBR
Reinforcement: High tensile textile cords - antistatic wire
Cover: Red CR - abrasion, ozone and hydrocarbon resistant
Use: General purpose fuel and oil delivery
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		⌚		⌒		⌘		⚡	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
25	1	35	1,38	10	150				0,650	0,440	
32	1 1/4	42	1,65	10	150				0,790	0,535	
38	1 1/2	48	1,89	10	150				0,920	0,620	
32	1 1/4	44	1,73	10	150				0,960	0,650	
38	1 1/2	50	1,97	10	150				1,110	0,750	
NA	LA	NEU	EMEA	SA	AP	AU					



650AB
Fuel-oil delivery 10 bar (150 psi)

Tube: Black conductive NBR
Reinforcement: High tensile textile cords - antistatic wire
Cover: Grey CR - abrasion, ozone and hydrocarbon resistant
Use: General purpose fuel and oil delivery
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)