

↔		↔		⌚	⌚	⌒		⌒	⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
152	6	166	6,54	5	75	760	30,00	80	6,140	4,130
203	8	221	8,70	5	75	1015	40,00	70	10,500	7,060
NA		LA	NEU	EMEA		SA	AP	AU		



204AA Water S&D 5 bar (75 psi)

Tube: Black SBR
Reinforcement: High tensile textile cords with embedded steel helix wire
Cover: Black SBR - abrasion and ozone resistant
Use: Water suction and delivery
Safety factor: 3:1 254 mm 2:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		⌚	⌚	⌒		⌒	⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
25	1	35	1,38	10	150	100	4,00	100	0,690	0,465
30	1 3/16	40	1,57	10	150	120	4,75	100	0,780	0,525
32	1 1/4	42	1,65	10	150	128	5,00	100	0,820	0,555
38	1 1/2	48	1,89	10	150	152	6,00	100	0,950	0,640
40	1 9/16	50	1,97	10	150	160	6,25	100	1,000	0,675
45	1 3/4	55	2,17	10	150	180	7,00	100	1,110	0,750
51	2	61	2,40	10	150	204	8,00	100	1,240	0,835
60	2 3/8	72	2,83	10	150	240	9,50	100	1,710	1,150
63	2 1/2	75	2,95	10	150	252	10,00	90	1,780	1,200
70	2 3/4	82	3,23	10	150	280	11,00	90	1,990	1,340
76	3	88	3,46	10	150	304	12,00	90	2,140	1,440
80	3 1/8	92	3,62	10	150	320	12,50	90	2,300	1,550
90	3 1/2	102	4,02	10	150	360	14,00	90	2,700	1,815
102	4	114	4,49	10	150	408	16,00	90	3,010	2,025
110	4 5/16	122	4,80	10	150	440	7,25	80	3,210	2,160
115	4 1/2	127	5,00	10	150	460	18,00	80	3,340	2,245
120	4 3/4	134	5,28	10	150	600	24,00	80	4,500	3,025
127	5	141	5,55	10	150	635	25,00	80	4,730	3,180
152	6	166	6,54	10	150	760	30,00	80	5,960	4,010
203	8	221	8,70	10	150	1015	40,00	70	9,810	6,595
254	10	272	10,71	10	150	1270	50,00	60	13,430	9,030
NA		LA	NEU	EMEA		SA	AP	AU		



202AA General purpose S&D 10 bar (150 psi) - EPDM

Tube: Black conductive EPDM
Reinforcement: High tensile textile cords with embedded steel helix wire
Cover: Black conductive EPDM - abrasion and ozone resistant
Use: Water suction and delivery. Also suitable for mild chemicals and fertilizers in general industrial and agricultural applications
Safety factor: ≤ 127 mm 3:1 ≥ 152 mm 2,5:1
Temperature: -40 °C +100 °C (-40 °F +212 °F)
 depending on conveyed chemical

↔		↔		⌚	⌚	⌒		⌒	⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
51	2	63	2,48	20	300	204	8,00	100	1,420	0,955
63	2 1/2	77	3,03	20	300	252	10,00	90	2,070	1,395
76	3	90	3,54	20	300	304	12,00	90	2,550	1,715
102	4	116	4,57	20	300	408	16,00	90	3,490	2,350
152	6	168	6,61	20	300	608	24,00	80	6,810	4,580
203	8	225	8,86	20	300	812	32,00	70	10,910	7,335
NA		LA	NEU	EMEA		SA	AP	AU		



223AA Water S&D 20 bar (300 psi) - heavy duty

Tube: Black conductive EPDM
Reinforcement: High tensile textile cords with embedded steel helix wire
Cover: Black conductive EPDM - abrasion and ozone resistant
Use: Water suction and delivery. Designed for long service life in heavy duty applications
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)