

| ↔ | | ↔ | | ⊥ | | ⌒ | | ⌘ | ♁ | |
|-----|--------|-----|------|-----|-----|-----|-------|-----|--------|-------|
| mm | inch | mm | inch | bar | psi | mm | inch | % | kg/m | lb/ft |
| 19 | 3/4 | 29 | 1,14 | 10 | 150 | 76 | 3,00 | 100 | 0,610 | 0,410 |
| 25 | 1 | 35 | 1,38 | 10 | 150 | 100 | 4,00 | 100 | 0,760 | 0,515 |
| 30 | 1 3/16 | 40 | 1,57 | 10 | 150 | 120 | 4,75 | 100 | 0,850 | 0,575 |
| 32 | 1 1/4 | 42 | 1,65 | 10 | 150 | 128 | 5,00 | 100 | 0,900 | 0,605 |
| 35 | 1 3/8 | 45 | 1,77 | 10 | 150 | 140 | 5,50 | 100 | 0,980 | 0,660 |
| 38 | 1 1/2 | 48 | 1,89 | 10 | 150 | 152 | 6,00 | 100 | 1,050 | 0,710 |
| 40 | 1 9/16 | 50 | 1,97 | 10 | 150 | 160 | 6,25 | 100 | 1,090 | 0,735 |
| 42 | 1 5/8 | 52 | 2,05 | 10 | 150 | 168 | 6,75 | 100 | 1,150 | 0,775 |
| 45 | 1 3/4 | 55 | 2,17 | 10 | 150 | 180 | 7,00 | 100 | 1,220 | 0,820 |
| 48 | 1 7/8 | 58 | 2,28 | 10 | 150 | 192 | 7,50 | 100 | 1,280 | 0,865 |
| 51 | 2 | 61 | 2,40 | 10 | 150 | 204 | 8,00 | 100 | 1,350 | 0,910 |
| 57 | 2 1/4 | 67 | 2,64 | 10 | 150 | 228 | 9,00 | 100 | 1,510 | 1,015 |
| 60 | 2 3/8 | 72 | 2,83 | 10 | 150 | 240 | 9,50 | 100 | 2,020 | 1,360 |
| 63 | 2 1/2 | 75 | 2,95 | 10 | 150 | 252 | 10,00 | 90 | 2,110 | 1,420 |
| 70 | 2 3/4 | 82 | 3,23 | 10 | 150 | 280 | 11,00 | 90 | 2,350 | 1,580 |
| 76 | 3 | 88 | 3,46 | 10 | 150 | 304 | 12,00 | 90 | 2,520 | 1,695 |
| 80 | 3 1/8 | 94 | 3,70 | 10 | 150 | 320 | 12,50 | 90 | 2,700 | 1,815 |
| 90 | 3 1/2 | 104 | 4,09 | 10 | 150 | 360 | 14,00 | 90 | 3,140 | 2,115 |
| 102 | 4 | 116 | 4,57 | 10 | 150 | 408 | 16,00 | 90 | 3,500 | 2,355 |
| 110 | 4 5/16 | 124 | 4,88 | 10 | 150 | 440 | 17,25 | 90 | 4,240 | 2,850 |
| 115 | 4 1/2 | 129 | 5,08 | 10 | 150 | 460 | 18,00 | 90 | 4,410 | 2,965 |
| 120 | 4 3/4 | 138 | 5,43 | 10 | 150 | 480 | 19,00 | 80 | 5,640 | 3,795 |
| 127 | 5 | 145 | 5,71 | 10 | 150 | 508 | 20,00 | 80 | 5,930 | 3,990 |
| 133 | 5 1/4 | 151 | 5,94 | 10 | 150 | 532 | 21,00 | 80 | 6,170 | 4,150 |
| 152 | 6 | 170 | 6,69 | 10 | 150 | 608 | 24,00 | 80 | 7,360 | 4,950 |
| 203 | 8 | 225 | 8,86 | 10 | 150 | 812 | 32,00 | 70 | 11,700 | 7,865 |

| | | | | | | |
|----|----|-----|------|----|----|----|
| NA | LA | NEU | EMEA | SA | AP | AU |
|----|----|-----|------|----|----|----|



605AA
Fuel-oil S&D 10 bar (150 psi)
exceed SAE 100R4
SAE J2006/R2 - ISO 13363/2/A+B

Tube: Black conductive NBR
Reinforcement: High tensile textile cords with embedded steel helix wire
Cover: Black CR - abrasion, ozone and hydrocarbon resistant
Use: Fuel and oil suction and delivery. Specially designed for tank truck and general industrial applications. Also suitable for marine wet exhaust and bilge pump connection
Safety factor: ≤ 127 mm 3:1 ≥ 133 mm 2,5:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

| ↔ | | ↔ | | ⊥ | | ⌒ | | ⌘ | ♁ | |
|-----|-------|-----|------|-----|-----|-----|-------|-----|-------|-------|
| mm | inch | mm | inch | bar | psi | mm | inch | % | kg/m | lb/ft |
| 38 | 1 1/2 | 48 | 1,89 | 10 | 150 | 152 | 6,00 | 100 | 1,080 | 0,730 |
| 51 | 2 | 61 | 2,40 | 10 | 150 | 204 | 8,00 | 100 | 1,390 | 0,935 |
| 76 | 3 | 88 | 3,46 | 10 | 150 | 304 | 12,00 | 90 | 2,580 | 1,735 |
| 102 | 4 | 116 | 4,57 | 10 | 150 | 408 | 16,00 | 90 | 3,580 | 2,410 |

| | | | | | | |
|----|----|-----|------|----|----|----|
| NA | LA | NEU | EMEA | SA | AP | AU |
|----|----|-----|------|----|----|----|



605AH
Fuel-oil S&D 10 bar (150 psi)

Tube: Black conductive NBR
Reinforcement: High tensile textile cords with embedded steel helix wire
Cover: Red CR - abrasion, ozone and hydrocarbon resistant
Use: Fuel and oil suction and delivery. Specially designed for tank truck and general industrial applications
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

| ↔ | | ↔ | | ⊥ | | ⌒ | | ⌘ | ♁ | |
|-----|-------|-----|------|-----|-----|-----|-------|-----|-------|-------|
| mm | inch | mm | inch | bar | psi | mm | inch | % | kg/m | lb/ft |
| 19 | 3/4 | 29 | 1,14 | 10 | 150 | 76 | 3,00 | 100 | 0,610 | 0,410 |
| 25 | 1 | 35 | 1,38 | 10 | 150 | 100 | 4,00 | 100 | 0,760 | 0,515 |
| 32 | 1 1/4 | 42 | 1,65 | 10 | 150 | 128 | 5,00 | 100 | 0,900 | 0,605 |
| 38 | 1 1/2 | 48 | 1,89 | 10 | 150 | 152 | 6,00 | 100 | 1,050 | 0,710 |
| 51 | 2 | 61 | 2,40 | 10 | 150 | 204 | 8,00 | 100 | 1,360 | 0,915 |
| 76 | 3 | 88 | 3,46 | 10 | 150 | 304 | 12,00 | 90 | 2,540 | 1,710 |
| 102 | 4 | 116 | 4,57 | 10 | 150 | 408 | 16,00 | 90 | 3,530 | 2,375 |

| | | | | | | |
|----|----|-----|------|----|----|----|
| NA | LA | NEU | EMEA | SA | AP | AU |
|----|----|-----|------|----|----|----|



629AA
Biofuel S&D 10 bar (150 psi)

Tube: Black conductive NBR
Reinforcement: High tensile textile cords with embedded steel helix wire
Cover: black CR - abrasion, ozone and hydrocarbon resistant
Use: Fuel and oil suction and delivery. Specially designed for biofuel and ethanol
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)