

↔		↔		⌚	⌚	↷		⌚	⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
25	1			7	100	150	6,00	90	0,540	0,365
32	1 1/4			6	90	192	7,50	90	0,680	0,460
38	1 1/2			6	90	228	9,00	90	0,760	0,515
40	1 9/16			6	90	240	9,50	90	0,800	0,540
51	2			5	75	306	12,00	90	1,150	0,775
60	2 3/8			4	60	360	14,00	90	1,550	1,045
63	2 1/2			4	60	378	15,00	90	1,600	1,080
76	3			4	60	456	18,00	90	2,000	1,345
80	3 1/8			4	60	480	19,00	90	2,100	1,415
102	4			3	45	612	24,00	90	3,100	2,085

NA LA NEU EMEA SA AP AU



668EL Fuel-oil S&D - PVC - heavy duty

Construction: Blue PVC - abrasion, ozone and hydrocarbon resistant
Reinforcement: White shock resistant rigid PVC
Use: General purpose fuel and oil suction and delivery
Safety factor: 3:1
Temperature: -10 °C +60 °C (+14 °F +140 °F)

↔		↔		⌚	⌚	↷		⌚	⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
51	2	61	2,40	10	150	255	10,00	100	1,380	0,930
76	3	88	3,46	10	150	380	15,00	90	2,570	1,730
102	4	116	4,57	10	150	510	20,00	90	3,560	2,395
152	6	168	6,61	10	150	760	30,00	80	6,820	4,585

NA LA NEU EMEA SA AP AU



601AA Oil rigger-fracking S&D 10 bar (150 psi)

Tube: Black NBR/PVC
Reinforcement: High tensile textile cords with embedded steel helix wire
Cover: Black SBR - abrasion and ozone resistant
Use: Crude oil mud in oilfield vacuum tank service. Extensively used in fracking operations
Safety factor: ≤ 102 mm 3:1 152 mm 2,5:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)