

| ↔ | | ↔ | | ⏚ | | ⤴ | | ⌘ | | ⏚ | |
|-----|------|-----|------|-----|-----|------|-------|-----|-------|-------|--|
| mm | inch | mm | inch | bar | psi | mm | inch | % | kg/m | lb/ft | |
| 51 | 2 | 77 | 3,03 | 35 | 525 | 204 | 8,00 | 100 | 3,020 | 2,030 | |
| 76 | 3 | 106 | 4,17 | 35 | 525 | 304 | 12,00 | 90 | 4,890 | 3,290 | |
| 102 | 4 | 134 | 5,28 | 35 | 525 | 408 | 16,00 | 90 | 7,250 | 4,875 | |
| NA | | LA | | NEU | | EMEA | | SA | | AP AU | |



776AA
Mineral sampling 35 bar (525 psi)

Tube: Black conductive NR - abrasion resistant
Reinforcement: High tensile textile cords with embedded steel helix wire
Cover: Black conductive SBR/NR - abrasion and ozone resistant
Use: Mineral recovery in sampling operations
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

| ↔ | | ↔ | | ⏚ | | ⤴ | | ⌘ | | ⏚ | |
|----|------|-----|------|-----|-----|------|-------|----|-------|-------|--|
| mm | inch | mm | inch | bar | psi | mm | inch | % | kg/m | lb/ft | |
| 76 | 3 | 106 | 4,17 | 35 | 525 | 304 | 12,00 | 90 | 4,850 | 3,260 | |
| NA | | LA | | NEU | | EMEA | | SA | | AP AU | |



776HA
Mineral sampling 35 bar (525 psi)

Tube: Red NR - abrasion resistant
Reinforcement: High tensile textile cords with embedded steel helix wire
Cover: Black conductive SBR/NR - abrasion and ozone resistant
Use: Mineral recovery in sampling operations
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

| ↔ | | ↔ | | ⏚ | | ⤴ | | ⌘ | | ⏚ | |
|-----|-------|-----|------|-----|-----|------|-------|----|-------|-------|--|
| mm | inch | mm | inch | bar | psi | mm | inch | % | kg/m | lb/ft | |
| 51 | 2 | 61 | 2,4 | 5 | 75 | 127 | 5,00 | 90 | 1,180 | 0,795 | |
| 63 | 2 1/2 | 75 | 2,95 | 5 | 75 | 157 | 6,50 | 90 | 1,850 | 1,245 | |
| 76 | 3 | 90 | 3,54 | 5 | 75 | 190 | 7,50 | 90 | 2,550 | 1,715 | |
| 102 | 4 | 116 | 4,57 | 5 | 75 | 255 | 10,00 | 90 | 3,560 | 2,395 | |
| 115 | 4 1/2 | 129 | 5,08 | 5 | 75 | 287 | 11,50 | 90 | 4,050 | 2,725 | |
| 127 | 5 | 141 | 5,55 | 5 | 75 | 318 | 13,00 | 80 | 4,680 | 3,150 | |
| 152 | 6 | 166 | 6,54 | 5 | 75 | 380 | 15,00 | 80 | 5,550 | 3,730 | |
| NA | | LA | | NEU | | EMEA | | SA | | AP AU | |



714HA
Drill cutting suction 5 bar (75 psi) - corrugated

Tube: Red NR - abrasion resistant
Reinforcement: High tensile textile cords with embedded steel helix wire - antistatic wire
Cover: Black conductive SBR/NR - abrasion and ozone resistant
Use: Bulk material suction and delivery. Specially designed for drill cutting suction in mobile drilling rigs. Corrugated construction for maximum flexibility
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)