

hose

↔		↔		⏱	⤴	⤵	⚖			
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
13	1/2	23	0,91	6	90				0,370	0,250
16	5/8	26	1,02	6	90				0,420	0,285
19	3/4	29	1,14	6	90				0,470	0,320
25	1	35	1,38	6	90				0,580	0,390
30	1 3/16	44	1,73	6	90				0,900	0,605
32	1 1/4	46	1,81	6	90				0,950	0,640
38	1 1/2	52	2,05	6	90				1,100	0,740
40	1 9/16	54	2,13	6	90				1,150	0,775
51	2	67	2,64	6	90				1,700	1,145

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



350AA
Steam 6 bar (90 psi)
hot water 15 bar (225 psi)

Tube: Black conductive EPDM
Reinforcement: High tensile textile cords
Cover: Black conductive EPDM - heat, abrasion and ozone resistant
Use: Saturated steam and hot water delivery in general industrial applications
Safety factor: Water 4:1 - Steam 10:1
Temperature: Water -40 °C +120 °C (-40 °F +248 °F)
 Steam +165 °C (+330 °F)

↔		↔		⏱	⤴	⤵	⚖			
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
13	1/2	25	0,98	6	90				0,430	0,290
16	5/8	30	1,18	6	90				0,600	0,405
19	3/4	33	1,30	6	90				0,680	0,460
25	1	40	1,57	6	90				0,900	0,605

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



354AA
Steam 6 bar (90 psi)
EN ISO 6134/1A

Tube: Black conductive EPDM
Reinforcement: High tensile textile cords
Cover: Black conductive EPDM - heat, abrasion and ozone resistant
Use: Saturated steam
Safety factor: 10:1
Temperature: -40 °C +165 °C (-40 °F +330 °F)

fittings

↔		↔		⏱	⤴	⤵	⚖			
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
13	1/2	23	0,91	6	90				0,390	0,265
16	5/8	26	1,02	6	90				0,450	0,305
19	3/4	31	1,22	6	90				0,640	0,435
25	1	37	1,46	6	90				0,800	0,540

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



350LL
Steam 6 bar (90 psi)
hot water 15 bar (225 psi)
FDA

Tube: White food grade EPDM
Reinforcement: High tensile textile cords
Cover: White EPDM - heat, abrasion and ozone resistant
Use: Saturated steam and hot water delivery in general industrial applications.
 Specially designed for wash down use in the food and dairy industry
Safety factor: Water 4:1 - Steam 10:1
Temperature: Water -40 °C +120 °C (-40 °F +248 °F)
 Steam +165 °C (+330 °F)

↔		↔		⏱	⤴	⤵	⚖			
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
13	1/2	23	0,91	6	90				0,370	0,250
16	5/8	26	1,02	6	90				0,430	0,290
19	3/4	31	1,22	6	90				0,600	0,405
25	1	37	1,46	6	90				0,740	0,500
32	1 1/4	46	1,81	6	90				0,930	0,625
38	1 1/2	52	2,05	6	90				1,090	0,735
51	2	67	2,64	6	90				1,660	1,120

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



350LE
Steam 6 bar (90 psi)
hot water 15 bar (225 psi)
FDA

Tube: White food grade EPDM
Reinforcement: High tensile textile cords
Cover: Blue EPDM - heat, abrasion and ozone resistant
Use: Saturated steam and hot water delivery in general industrial applications.
 Specially designed for wash down use in the food and dairy industry
Safety factor: Water 4:1 - Steam 10:1
Temperature: Water -40 °C +120 °C (-40 °F +248 °F)
 Steam +165 °C (+330 °F)

appendix