


PEAL® Black & Galvanised Mild Steel Reducing Socket

Black & Galvanised Mild Steel Reducing Socket						
AAP CODE		IMPERIAL SIZE	A	C	D	APPROX. (KG/PC)
BLACK	GALVANISED					
SS0806	SS0806G	1/4 X 1/8	25	15	19	0.03
SS1008	SS1008G	3/8 X 1/4	27	19	22	0.04
SS1508	SS1508G	1/2 X 1/4	36	22	28	0.08
SS1510	SS1510G	1/2 X 3/8	36	22	28	0.08
SS2008	SS2008G	3/4 X 1/4	39	30	34	0.16
SS2010	SS2010G	3/4 X 3/8	39	30	34	0.15
SS2015	SS2015G	3/4 X 1/2	39	30	34	0.14
SS2510	SS2510G	1 X 3/8	47	31	41	0.22
SS2515	SS2515G	1 X 1/2	47	31	41	0.2
SS2520	SS2520G	1 X 3/4	47	31	41	0.2
SS3220	SS3220G	1 1/4 X 3/4	57	38	50	0.36
SS3225	SS3225G	1 1/4 X 1	57	44	50	0.35
SS4020	SS4020G	1 1/2 X 3/4	60	38	57	0.43
SS4025	SS4025G	1 1/2 X 1	60	44	57	0.43
SS4032	SS4032G	1 1/2 X 1 1/4	60	50	57	0.4
SS5020	SS5020G	2 X 3/4	63	38	69	0.6
SS5025	SS5025G	2 X 1	63	44	69	0.6
SS5032	SS5032G	2 X 1 1/4	63	50	69	0.6
SS5040	SS5040G	2 X 1 1/2	63	57	69	0.6
SS6540	SS6540G	2 1/2 X 1 1/2	69	57	88	1
SS6550	SS6550G	2 1/2 X 2	69	69	88	1
SS8025	SS8025G	3 X 1	79	44	101	1.5
SS8050	SS8050G	3 X 2	79	69	101	1.25
SS8065	SS8065G	3 X 2 1/2	79	88	101	1.26
SS9450	SS9450G	4 X 2	84	69	127	2.2
SS9465	SS9465G	4 X 2 1/2	84	88	127	2.48
SS9480	SS9480G	4 X 3	84	101	127	2.14



PEAL® Black Mild Steel Half Socket (Type Heavy)

Black Mild Steel Half Socket (Type Heavy)				
AAP CODE	IMPERIAL SIZE	A	C	APPROX. (KG/PC)
SSH10	3/8	12.2	22.0	0.02
SSH15	1/2	16.0	27.0	0.03
SSH20	3/4	19.1	32.5	0.04
SSH25	1	21.1	39.5	0.06
SSH32	1 1/4	28.1	49.0	0.11
SSH40	1 1/2	25.3	56.0	0.17
SSH50	2	28.3	68.0	0.20
SSH65	2 1/2	30.6	84.0	0.38
SSH80	3	35.7	98.0	0.43
SSH94	4	40.4	124.0	0.80

