

**HIGH PRESSURE HOSE**
**M4K-XTF**

TWO WIRE BRAID HOSE

BRAIDED WIRE REINFORCED HOSE - SAE 100R19

EXTRATUFF COVER



Part Number	Internal Size	Internal DN	Internal Diameter - inches	External Diameter - inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min. bend radius - inches	Min bend radius - mm
4M4K-XTF	04	6	1/4	0.55	14	4000	280	16000	1120	1.5	38
6M4K-XTF	06	10	3/8	0.7	17.8	4000	280	16000	1120	2.0	50
8M4K-XTF	08	12	1/2	0.82	20.8	4000	280	16000	1120	2.8	70
10M4K-XTF	10	16	5/8	0.99	25.1	4000	280	16000	1120	3.0	75
12M4K-XTF	12	19	3/4	1.17	29.7	4000	280	16000	1120	3.8	95
16M4K-XTF	16	25	1	1.52	38.6	4000	280	16000	1120	4.5	115

† - Please contact Hydraulink for further details and availability.

Pricing current as at 14 Feb 2017 and excludes GST. Hydraulink reserve the right to change pricing and technical specifications without notice.