

HIGH PRESSURE HOSE

G2

TWO WIRE BRAID HOSE

BRAIDED WIRE REINFORCED HOSE - SAE 100R2 Type AT



Part Number	Internal Size	Internal DN	Internal Diameter - inches	External Diameter - inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min. bend radius - inches	Min bend radius - mm
3G2	03	5	3/16	0.52	13.2	6000	415	24000	1660	3.5	90
4G2	04	6	1/4	0.58	15	5800	400	23200	1600	4	100
5G2	05	8	5/16	0.64	16.3	5100	350	20300	1400	4.3	110
6G2	06	10	3/8	0.73	18.8	4800	330	19200	1320	5	127
8G2	08	12	1/2	0.86	21.8	4000	275	16000	1120	7	180
10G2	10	16	5/8	0.98	25.1	3625	250	14500	1000	8	200
12G2	12	19	3/4	1.14	29	3100	215	12400	860	9.5	240
16G2	16	25	1	1.48	37.6	2400	165	9600	660	12	305
20G2	20	31	1.1/4	1.87	47.5	1825	125	7300	500	16.5	420
24G2	24	38	1.1/2	2.15	54.6	1300	90	5200	360	20	510
32G2	32	51	2	2.65	67.3	1175	80	4700	320	25	635

† - Please contact Hydraulink for further details and availability.

Pricing current as at 14 Feb 2017 and excludes GST. Hydraulink reserve the right to change pricing and technical specifications without notice.