

| ↔ | | ↔ | | ⌚ | | ⤴ | | ⌚ | | ⚖ | |
|----|-------|----|------|-----|-----|----|------|---|-------|-------|--|
| mm | inch | mm | inch | bar | psi | mm | inch | % | kg/m | lb/ft | |
| 38 | 1 1/2 | 62 | 2,44 | 14 | 200 | | | | 2,210 | 1,490 | |
| 51 | 2 | 75 | 2,95 | 14 | 200 | | | | 2,840 | 1,910 | |

| | | | | | | |
|----|----|-----|------|----|----|----|
| NA | LA | NEU | EMEA | SA | AP | AU |
|----|----|-----|------|----|----|----|



756AA
Gunite 14 bar (200 psi) - FRAS
exceeds AS 2660/C

Tube: Black conductive NR - abrasion resistant
Reinforcement: High tensile textile cords
Cover: Black conductive SBR - abrasion, ozone and fire resistant
Use: Gunite
Safety factor: 4:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

| ↔ | | ↔ | | ⌚ | | ⤴ | | ⌚ | | ⚖ | |
|----|-------|----|------|-----|-----|----|------|---|-------|-------|--|
| mm | inch | mm | inch | bar | psi | mm | inch | % | kg/m | lb/ft | |
| 32 | 1 1/4 | 46 | 1,81 | 7 | 100 | | | | 0,920 | 0,620 | |
| 38 | 1 1/2 | 52 | 2,05 | 7 | 100 | | | | 1,070 | 0,720 | |
| 51 | 2 | 65 | 2,56 | 7 | 100 | | | | 1,410 | 0,950 | |

| | | | | | | |
|----|----|-----|------|----|----|----|
| NA | LA | NEU | EMEA | SA | AP | AU |
|----|----|-----|------|----|----|----|



765AA
Stone dust 7 bar (100 psi) - FRAS
AS 2660/C

Tube: Black conductive SBR/NR - abrasion resistant
Reinforcement: High tensile textile cords
Cover: Black conductive SBR - abrasion, ozone and fire resistant
Use: "Stone dusting" in underground mines. Also suitable for air and water delivery
Safety factor: 4:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

| ↔ | | ↔ | | ⌚ | | ⤴ | | ⌚ | | ⚖ | |
|-----|------|-----|-------|----|-----|-----|------|-------|----|--------|--------|
| mm | inch | mm | inch | mm | bar | psi | mm | inch | % | kg/m | lb/ft |
| 51 | 2 | 69 | 2,72 | 4 | 10 | 150 | 204 | 8,00 | 90 | 2,080 | 1,400 |
| 76 | 3 | 100 | 3,94 | 6 | 10 | 150 | 304 | 12,00 | 90 | 4,220 | 2,840 |
| 102 | 4 | 126 | 4,96 | 6 | 10 | 150 | 408 | 16,00 | 90 | 5,650 | 3,800 |
| 127 | 5 | 155 | 6,10 | 6 | 10 | 150 | 635 | 25,00 | 80 | 7,900 | 5,310 |
| 152 | 6 | 182 | 7,17 | 7 | 10 | 150 | 760 | 30,00 | 80 | 10,300 | 6,925 |
| 203 | 8 | 235 | 9,25 | 7 | 10 | 150 | 1015 | 40,00 | 70 | 14,420 | 9,695 |
| 254 | 10 | 286 | 11,26 | 7 | 10 | 150 | 1270 | 50,00 | 60 | 20,450 | 13,745 |
| 305 | 12 | 343 | 13,50 | 9 | 10 | 150 | 1500 | 60,00 | 60 | 29,800 | 20,030 |

| | | | | | | |
|----|----|-----|------|----|----|----|
| NA | LA | NEU | EMEA | SA | AP | AU |
|----|----|-----|------|----|----|----|



706AA
Abrasive slurry S&D 10 bar (150 psi)
muff couplings

Tube: Black conductive NR. Abrasion resistance 50 mm³ (ISO 4649/A)
Reinforcement: High tensile textile cords with embedded steel helix wire
Cover: Black conductive SBR/NR - abrasion and ozone resistant
Use: Bulk material and abrasive slurries suction and delivery in heavy duty mining. Designed for muff coupling use
Safety factor: ≤ 127 mm 3:1 ≥ 152 mm 2,5:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)