

↔		↔		⌚		⤴		⌚		⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
5	3/16	12	0,47	12	180	50	2,00		0,140	0,095	
NA	LA	NEU	EMEA	SA	AP	AU					



071AI
LPG welding 12 bar (180 psi)
AS 1335

Tube: Black NBR
Reinforcement: High tensile textile cords
Cover: Orange SBR/EPDM - abrasion and ozone resistant
Use: LPG welding
Safety factor: 4:1
Temperature: -25 °C +80 °C (-13 °F +176 °F)

↔		↔		⌚		⤴		⌚		⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
5	3/16	12	0,47	12	180	50	2,00		0,280	0,190	
NA	LA	NEU	EMEA	SA	AP	AU					



071EH
Oxygen/acetylene twin welding 12 bar (180 psi)
AS 1335

Tube: Black SBR
Reinforcement: High tensile textile cords
Cover: Blue, red SBR/EPDM - abrasion and ozone resistant
Use: Oxygen/Acetylene twin welding
Safety factor: 3:1
Temperature: -25 °C +80 °C (-13 °F +176 °F)

↔		↔		⌚		⤴		⌚		⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
5	3/16	12	0,47	12	180	50	2,00		0,280	0,190	
NA	LA	NEU	EMEA	SA	AP	AU					



071EI
Oxygen/LPG twin welding 12 bar (180 psi)
AS 1335

Tube: Black SBR-NBR
Reinforcement: High tensile textile cords
Cover: Blue, orange SBR/EPDM - abrasion and ozone resistant
Use: Oxygen/LPG twin welding
Safety factor: 4:1
Temperature: -25 °C +80 °C (-13 °F +176 °F)

hose

fittings

appendix