

↔		↔		⌚		⤴		⌚		⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
6	1/4	13	0,51	20	300	48	2,00		0,140	0,095	
8	5/16	15	0,59	20	300	64	2,50		0,170	0,115	
10	3/8	17	0,67	20	300	80	3,00		0,205	0,140	
13	1/2	21	0,83	20	300	104	4,00		0,275	0,185	
16	5/8	25	0,98	20	300	128	5,00		0,375	0,255	
19	3/4	29	1,14	20	300	152	6,00		0,505	0,340	
25	1	35	1,38	20	300	200	8,00		0,627	0,421	
NA	LA	NEU	EMEA	SA	AP	AU					



984AH Multipurpose 20 bar (300 psi)

Tube: Black synthetic elastomer
Reinforcement: High tensile textile cords
Cover: Red synthetic elastomer with longitudinal blue stripes - abrasion, ozone and hydrocarbon resistant
Use: Compressed air, water, fuel and oil delivery in general industrial applications
Safety factor: 3:1
Temperature: -10 °C +60 °C (+14 °F +140 °F)

↔		↔		⌚		⤴		⌚		⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
6	1/4	13	0,51	17	255	48	2,00		0,120	0,080	
10	3/8	17	0,67	17	255	64	2,50		0,250	0,170	
13	1/2	21	0,83	17	255	104	4,00		0,360	0,245	
16	5/8	25	0,98	17	255	128	5,00		0,420	0,285	
19	3/4	29	1,14	17	255	152	6,00		0,540	0,365	
25	1	35	1,38	17	255	200	8,00		0,730	0,495	
NA	LA	NEU	EMEA	SA	AP	AU					



974AH Multipurpose 17 bar (250 psi) - non conductive

Tube: Black non conductive NBR (RMA Class A)
Reinforcement: High tensile textile cords
Cover: Red NBR/PVC (RMA Class B) - abrasion, ozone and hydrocarbon resistant
Use: Premium quality compressed air, water, fuel and oil delivery in general industrial applications
Safety factor: 4:1
Temperature: -25 °C +80 °C (-13 °F +176 °F)

↔		↔		⌚		⤴		⌚		⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
6	1/4	16	0,63	20	300	48	2,00		0,240	0,160	
10	3/8	18	0,71	20	300	80	3,00		0,270	0,180	
13	1/2	21	0,83	20	300	104	4,00		0,370	0,250	
19	3/4	29	1,14	20	300	152	6,00		0,620	0,420	
25	1	36	1,42	20	300	200	8,00		0,940	0,635	
NA	LA	NEU	EMEA	SA	AP	AU					



975AH Multipurpose 20 bar (300 psi) - non conductive

Tube: Black non conductive NBR (RMA Class A)
Reinforcement: High tensile textile cords
Cover: Red NBR/PVC (RMA Class A) - abrasion, ozone and hydrocarbon resistant
Use: Premium quality compressed air, water, fuel and oil delivery in general industrial applications
Safety factor: 4:1
Temperature: -25 °C +80 °C (-13 °F +176 °F)

↔		↔		⌚		⤴		⌚		⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
32	1 1/4	44	1,73	20	300				0,990	0,670	
38	1 1/2	50	1,97	20	300				1,150	0,775	
51	2	65	2,56	20	300				1,510	1,015	
NA	LA	NEU	EMEA	SA	AP	AU					



954AH Multipurpose 20 bar (300 psi) - non conductive

Tube: Black non conductive NBR
Reinforcement: High tensile textile cords
Cover: Red NBR/PVC - abrasion, ozone and hydrocarbon resistant
Use: Premium quality compressed air, water, fuel and oil delivery in general industrial applications
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)