

↔		↔		⊕		⌒		⌒		⊞	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
13	1/2	19	0,75	10	150	130	5,00		0,240	0,160	
16	5/8	22	0,87	10	150	160	6,25		0,280	0,190	
19	3/4	27	1,06	10	150	190	7,50		0,450	0,305	
25	1	33	1,30	10	150	250	10,00		0,570	0,385	

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



375AA

Hot water-car heater 10 bar (150 psi)

Tube: Black EPDM

Reinforcement: High tensile textile cords

Cover: Black EPDM - heat, abrasion and ozone resistant

Use: General purpose-hot water.

Specially designed for automotive heating systems

Safety factor: 3:1

Temperature: -35 °C +100 °C (-31 °F +212 °F)

↔		↔		⊕		⌒		⌒		⊞	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
13	1/2	21	0,83	5	75				0,280	0,190	
16	5/8	24	0,94	5	75				0,330	0,225	
18	23/32	26	1,02	5	75				0,360	0,245	
20	13/16	28	1,10	5	75				0,390	0,265	
22	7/8	30	1,18	5	75				0,420	0,285	
25	1	33	1,30	5	75				0,470	0,320	
28	1 1/8	36	1,42	5	75				0,510	0,345	
30	1 3/16	38	1,50	5	75				0,540	0,365	
32	1 1/4	40	1,57	5	75				0,570	0,385	
35	1 3/8	43	1,69	5	75				0,620	0,420	
38	1 1/2	48	1,89	5	75				0,850	0,575	
40	1 9/16	50	1,97	5	75				0,890	0,600	
42	1 5/8	52	2,05	5	75				0,930	0,625	
45	1 3/4	55	2,17	5	75				0,980	0,660	
48	1 7/8	58	2,28	5	75				1,040	0,700	
51	2	61	2,40	5	75				1,110	0,750	
55	2 1/6	65	2,56	5	75				1,180	0,795	
57	2 1/4	67	2,64	5	75				1,220	0,820	
60	2 3/8	70	2,76	5	75				1,280	0,865	
63	2 1/2	73	2,87	5	75				1,340	0,905	
70	2 3/4	80	3,15	5	75				1,440	0,970	
76	3	86	3,39	5	75				1,550	1,045	
80	3 1/8	90	3,54	5	75				1,630	1,100	
90	3 1/2	102	4,02	5	75				2,010	1,355	
102	4	114	4,49	5	75				2,250	1,515	
110	4 5/16	122	4,80	5	75				2,410	1,620	
115	4 1/2	127	5,00	5	75				2,510	1,690	
127	5	141	5,55	5	75				3,200	2,155	

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



352AA

Radiator 5 bar (75 psi)

exceeds DIN 73411 SAE 20R1 D-2

Tube: Black EPDM

Reinforcement: High tensile textile cords

Cover: Black EPDM - heat, abrasion and ozone resistant

Use: Radiator

Safety factor: 3:1

Temperature: -40 °C +120 °C (-40 °F +248 °F)

hose

fittings

appendix