

Anchorage

Webbing Anchor Straps and Slings



- Webbing anchor slings and straps provide an economical and portable anchorage system
- Slings provide a closed loop webbing configuration, where the straps provide a protective sleeve with loop through or coupled D-ring configuration
- Complies with AS/NZS 1891.4:2009

PART NO:	Description
10112987	1.5M, Anchor Sling
10112988	2.0M, Anchor Sling
229829-1.0MT	1.0M, Anchor Strap
229829-1.5MT	1.5M, Anchor Strap
229829-2.0MT	2.0M, Anchor Strap

D-Plate Anchorage Connector



- Provides a permanent anchorage point
- Rated to 22.2kN
- Bolts to beams or columns
- Also available with 8" x 8" back plate made of black anodised aluminium for attachment to concrete walls
- Complies with AS/NZS 1891.4:2009

PART NO:	Description
506632	D-Plate

Workman® FP Stryder



- The Workman® FP Stryder is a portable beam grip that is an approved anchorage connection when installed on a beam flange
- Low friction Teflon wear plates allow the Stryder to glide effortlessly along the beam
- Vernier push button adjustability ensures secure fit and can be adjusted with one hand – no extra tools required
- Integral load indicator shows if the Stryder has been subject to a fall
- Lightweight design - PN: 10144431 (2.3kg) and PN: 10144432 (5.4kg)
- Mounting can be overhead or at workers foot level
- Two versions offered to suit different beam flange sizes
- 182kg working capacity and rated to 22.2kN
- Complies with AS/NZS 1891.4:2009

PART NO:	Description
10144431	4"-13.5" Beam
10144432	14"-23.5" Beam

Bolt D Ring Anchorage Connector



- Provides permanent anchorage point
- Designed for horizontal installation
- Rated to 22.2kN
- Bolts to beams or girders
- Uses single 5/8" Grade 8 bolt (not supplied)
- Complies with AS/NZS 1891.4:2009

PART NO:	Description
10003213	Bolt D Ring