

WARRIOR™ 400i CC/CV

Robust inverter welding packages



MIG

STICK

TIG

GOUGING

WARRIOR™ 400i CC/CV POWER SOURCE



FEATURES	BENEFITS
Multi-Process	Includes MIG, Flux-Cored, Stick with Standard Compliant VRD, Live TIG Start and Arc Gouging gives you the flexibility at work: <ul style="list-style-type: none"> • Flux-Cored and Solid wire, 0.8 -1.6 mm. • Carbon Arc Gouging up to 8.0mm (5/16in.). • 6010 (cellulose) capability.
High Duty cycle	For long runs and various applications giving high productivity.
Durable and rugged	IP23 rating for outdoor and indoor use in rough environment.
Easy to use	Simple and clear user interface for everyone to get started quickly.
Robust and ergonomic handles	Also for mechanical lifting.
Sun friendly display	Easy to read outdoors.
Inverter technology	Smaller, lighter and less energy cost, gives you value for money.
Generator compatible	For flexible use in different job sites.
Automatic Hot Start/Variable Arc Control	To support your different demands.
Wide input voltage range	342V to 456V to accommodate variation in the power grid or generators.

QUALITY AND ENVIRONMENT	APPLICATIONS
<p>IP23 rated - Withstands rain with the fan on.</p> <p>Air tunnel design - Clean and dirty side in the machine to ensure long-term reliability.</p> <p>Autofan - Reduces energy consumption and dirt intake.</p> <p>3 years warranty.</p>	<ul style="list-style-type: none"> • Fabrication • Construction • Pipe Line • Mobile Machinery • Outstanding Gouging Capability • Ship Building • Energy Generation • Repair & Maintenance • Rental

WARRIOR™ FEED 304 - WIRE FEEDER AND OPTIONS



The new user friendly and robust feeder.

- **Rugged design** – Handle, connectors for tough use.
- **4 roll drive with tacho feedback** – For superior wire feeding.
- **Sun-friendly display** – Easy to read outdoor.
- **Bobbin cover** – Included standard feature for protection.
- **Voltage Pre-set** – Support the setting of welding parameters.

Cooling unit
Cool 2

Trolley/Wheel kits
Trolley
Wheel kit power source
Wheel kit feeder

* For more options and ordering information, please see last page.

WARRIOR™ MAIN CONTROLS



WARRIOR™ 400i CC/CV



- 1. Power On/Off
- 2. Wire feeder control connector
- 3. Resettable Circuit Breaker
- 4. Output Power Connector (+)

- 5. Output Power Connector (-)
- 6. Over Temperature indicator
- 7. VRD indicator in Stick mode
- 8. Digital Volt/Amp Meter

- 9. Output Voltage / Current Control
- 10. Stick electrode type Selector
- 11. Inductance/Arc Force Control
- 12. Welding Process Selector

TECHNICAL DATA WARRIOR™ 400i CC/CV

Mains Supply, VAC, 3 ph 50/60Hz	380-400-415, +/-10%
Mains cable, Ø mm ²	4 x 6
Fuse, Motor Start Type or Circuit Breaker Type C, A	20
Maximum load at:	
100% duty cycle A/V, 3ph	300/32
60% duty cycle A/V, 3ph	400/36
Setting range A	
MIG/FCAW	16-400
Stick (MMAW)	16-400
TIG	5-400
Open circuit voltage, V	56
Open circuit voltage (VRD ON), V	<35
Idle Power, W	120
Efficiency at max. current %	88
Power factor at max current	0.92
Enclosure class	IP23
Dimensions (l x w x h mm)	712 x 325 x 470
with cooling unit (l x w x h mm)	712 x 325 x 700
Weight, kg	52
With cooling unit excl coolant, kg	67
Operating Temperature, °C	-10 to +40
Application class	S

TECHNICAL DATA, WARRIOR™ FEED 304

Power supply, VAC	42
Wire spool capacity, kg	18
Max. spool diameter, mm	300
Wire feed speed, m/min	1.5 - 25.0
Dimension incl. bobbin cover (l x w x h mm)	675 x 264 x 418
Weight incl. bobbin cover, kg	14.5
Wire dimensions:	
Steel	0.6-1.6
Stainless steel	0.6-1.6
Aluminium	0.8-1.6
Cored wire	0.9-1.6
Enclosure class	IP23

TECHNICAL DATA, COOL 2 COOLING UNIT

Power supply, from power source	40V, 50/60Hz
Coolant flow capacity, l/min	1.8
Cooling power, kW	1.0
Max pressure, bar	4.6
Max pressure height to torch, m	8.5
Weight / incl. coolant, kg	15 / 19
Dimensions incl. filler tube l x w x h mm	680 x 325 x 230
Enclosure class	IP23

Cool 2 cooling unit is rated 500 A at 60% duty cycle at 25°C ambient temperature.



CIGWELD Pty Ltd
CIGWELD An ESAB Brand
 71 Gower Street, Preston VIC 3072 Australia

Customer Care
 Tel: 1300 654 674 | Fax: 03 9474 7391
 Email: enquiries@cigweld.com.au

International Enquiries
 Tel: +61 3 9474 7508 | Fax: +61 3 9474 7488

 **CIGWELD.COM.AU | ESAB.COM**

ORDERING INFORMATION

WARRIOR™ 400i CC/CV, 380-415V 0465 350 886
 Supplied with 3m mains cable

Choose one of the following:

WARRIOR™ Feed 304 0465 250 880
 WARRIOR™ Feed 304w, water 0465 250 881

ORDERING INFORMATION, CONNECTION CABLES FOR WARRIOR FEED

Select required size and length:

Air cooled 70 mm²

Connection cable 2m 0459 836 880
 Connection cable 5m 0459 836 881
 Connection cable 10m 0459 836 882
 Connection cable 15m 0459 836 883
 Connection cable 25m 0459 836 884
 Connection cable 35m 0459 836 885

Water cooled 70 mm²

Connection cable 2m 0459 836 890
 Connection cable 5m 0459 836 891
 Connection cable 10m 0459 836 892
 Connection cable 15m 0459 836 893
 Connection cable 25m 0459 836 894
 Connection cable 35m 0459 836 895

ORDERING INFORMATION, TORCHES

Select required size and length:

PSF™ 405, 3m Mig Gun 0458 401 882
 PSF™ 405, 4.5m Mig Gun 0458 401 883
 PSF™ 505, 3m Mig Gun 0458 401 884
 PSF™ 505, 4.5m Mig gun 0458 401 885
 TXH™ 201V, OKC 4m Tig Torch 0700 300 553

ORDERING INFORMATION, OPTIONS


Trolley 0465 510 880

Remote units

M1 for MIG 8pin; requires cable & Wirefeeder outlet kit 0459 491 895
 Remote outlet kit 23pin - Wirefeeder 0465 451 880
 Remote cable - 5m; 8pin to 23pin suits M1 remote 0459 553 880
 AT1 for MMAW/TIG 8pin; requires cable & power source outlet kit 0459 491 896
 AT1 CoarseFine for MMAW/TIG 8pin; requires cable & power source outlet kit 0459 491 897
 Remote outlet kit - power source 0465 424 880
 Remote cable - 5m; 8pin to 12pin suits AT1 remote 0459 552 880
 Remote cable - 10m; 8pin to 12pin suits AT1 remote 0459 552 881
 Remote cable - 25m; 8pin to 12pin suits AT1 remote 0459 552 883

Cool 2, water cooler 0465 427 880
 Wheel Kit, power source 0465 416 880
 Wheel kit, WARRIOR™ feeder 0458 707 880

These welding power sources comply with the requirements of IEC/EN 60974-1 as well as IEC/EN 60974-2 and EN 60974-10

The symbol  indicates that the welding power source may be used in areas with an increased electrical hazard, i.e. areas where the electrical hazard is increased due to damp and/or the proximity to earthed metal objects.