

↔		↔		⌚		⌒		⌘		⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
25	1	37	1,46	16	240	125	5,00		0,810	0,545	
32	1 1/4	44	1,73	16	240	160	6,25		0,970	0,655	
35	1 3/8	47	1,85	16	240	175	7,00		1,040	0,700	
38	1 1/2	51	2,01	16	240	190	7,50		1,130	0,760	
51	2	67	2,64	16	240	255	10,00		1,660	1,120	

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



**658AA**  
**Domestic fuel reeling 16 bar (240 psi)**  
**textile braided**  
**EN 1360/1 TRbF 131/2**

**Tube:** Black conductive NBR  
**Reinforcement:** High tensile textile braids  
**Cover:** Black conductive CR - abrasion, ozone, hydrocarbon and fire resistant  
**Use:** Fuel and oil delivery in heavy duty reeling applications. Also suitable for tank cleaning.  
 Antistatic wire available on request  
**Safety factor:** 3:1  
**Temperature:** -30 °C +70 °C (-22 °F +158 °F)

↔		↔		⌚		⌒		⌘		⌚	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
19	3/4	31	1,22	25	375	160	6,25		0,630	0,425	
25	1	38	1,50	25	375	200	8,00		0,810	0,545	
32	1 1/4	45	1,77	25	375	250	10,00		0,950	0,640	
38	1 1/2	52	2,05	25	375	320	12,50		1,350	0,910	
51	2	67	2,64	25	375	400	16,00		2,030	1,365	

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



**659AA**  
**LPG delivery 25 bar (375 psi) - textile braided**  
**EN 1762/DM**

**Tube:** Black NBR  
**Reinforcement:** High tensile textile braids - antistatic wire  
**Cover:** Black CR - abrasion, ozone, hydrocarbon and fire resistant - pin pricked  
**Use:** LPG delivery in heavy duty reeling applications  
**Safety factor:** 4:1  
**Temperature:** -30 °C +70 °C (-22 °F +158 °F)