


732/40 Ring insert tools

AS-drive



| Code | mm | mm | b mm | h mm | S mm | Δg |
|-------------|----|-------|------|------|------|-----|
| 58 22 40 13 | 13 | 14x18 | 22.5 | 11 | 25 | 130 |
| 58 22 40 14 | 14 | 14x18 | 23 | 11 | 25 | 123 |
| 58 22 40 15 | 15 | 14x18 | 24 | 11 | 25 | 128 |
| 58 22 40 16 | 16 | 14x18 | 25.5 | 12 | 25 | 133 |
| 58 22 40 17 | 17 | 14x18 | 27 | 12 | 25 | 135 |
| 58 22 40 18 | 18 | 14x18 | 29 | 13 | 25 | 134 |
| 58 22 40 19 | 19 | 14x18 | 30.5 | 13 | 25 | 138 |
| 58 22 40 21 | 21 | 14x18 | 33 | 15 | 25 | 144 |
| 58 22 40 22 | 22 | 14x18 | 34.5 | 15 | 25 | 145 |
| 58 22 40 24 | 24 | 14x18 | 37.5 | 15 | 25 | 153 |
| 58 22 40 27 | 27 | 14x18 | 42.5 | 17 | 25 | 162 |
| 58 22 40 28 | 28 | 14x18 | 45.5 | 19 | 25 | 175 |
| 58 22 40 30 | 30 | 14x18 | 46 | 19 | 25 | 182 |
| 58 22 40 32 | 32 | 14x18 | 47.5 | 19 | 25 | 181 |
| 58 22 40 34 | 34 | 14x18 | 52 | 19 | 28* | 210 |
| 58 22 40 36 | 36 | 14x18 | 54 | 19 | 28* | 203 |
| 58 22 40 41 | 41 | 14x18 | 60 | 20 | 30* | 240 |


* Caution! Modified settings on torque wrench (refer to note on page 197).

732a/40 Ring insert tools

AS-drive

| Code | " | mm | b mm | h mm | S mm | Δg |
|-------------|-------|-------|------|------|------|-----|
| 58 62 40 32 | 1/2 | 14x18 | 22.5 | 11 | 25 | 122 |
| 58 62 40 34 | 9/16 | 14x18 | 23 | 11 | 25 | 122 |
| 58 62 40 36 | 5/8 | 14x18 | 25.5 | 12 | 25 | 134 |
| 58 62 40 38 | 11/16 | 14x18 | 29 | 13 | 25 | 132 |
| 58 62 40 40 | 3/4 | 14x18 | 30.5 | 13 | 25 | 138 |
| 58 62 40 42 | 13/16 | 14x18 | 33 | 15 | 25 | 142 |
| 58 62 40 44 | 7/8 | 14x18 | 34.5 | 15 | 25 | 147 |
| 58 62 40 46 | 15/16 | 14x18 | 37.5 | 15 | 25 | 151 |
| 58 62 40 48 | 1 | 14x18 | 41 | 17 | 25 | 160 |

732TX/40 TORX® insert tools



| Code | size | mm | b mm | h mm | S mm | Δg |
|-------------|------|-------|------|------|------|-----|
| 58 29 40 14 | E14 | 14x18 | 22.5 | 11 | 25 | 130 |
| 58 29 40 18 | E18 | 14x18 | 24 | 11 | 25 | 135 |
| 58 29 40 20 | E20 | 14x18 | 29 | 13 | 25 | 150 |
| 58 29 40 24 | E24 | 14x18 | 30.5 | 13 | 25 | 150 |

7370/40-1 Adaptor

for using shell tools with an internal square drive of 24.5 x 28 mm on torque wrenches with an internal square drive of 14 x 18 mm. Caution! Modified settings on torque wrench (refer to note on p. 197).



| Code | mm | mm | L mm | Δg |
|-------------|-------|---------|------|-----|
| 58 29 00 41 | 14x18 | 24,5x28 | 66 | 251 |

736/40 BIT holder insert tool

Internal hex drive with a collar-thrust spring. Bits are easy to insert, lock securely in position and can be removed just as easily; even hex bits with a wide groove (Type E, DIN 3126/ISO 1173).




| Code | inside | " | mm | b mm | h mm | S mm | Δg |
|-------------|--------|------|-------|------|------|------|-----|
| 58 26 10 40 | D 8 | 5/16 | 14x18 | 16 | 12.5 | 25 | 112 |

inside ○ DIN 3126/ISO 1173

737/40 Blank end insert tool

gunmetal finish. To prevent damage from excessive temperatures, the locking pin, spring and washer are not fitted until the welding work has been completed. Instructions are supplied.




| Code | Welding surface | mm | H mm | L mm | Δg |
|-------------|-----------------|-------|------|------|----|
| 58 27 00 40 | h x b mm | 14x18 | 21.5 | 12 | 98 |

7370/40 Adaptor




for using insert tools with an outer square drive of 9 x 12 mm on torque wrenches with an internal square drive of 14 x 18 mm. Caution! Modified settings on torque wrench (refer to note on p. 197).



| Code | mm | mm | b mm | h mm | S mm | Δg |
|-------------|-------|------|------|------|------|-----|
| 58 29 00 40 | 14x18 | 9x12 | 28 | 21 | 21.5 | 115 |

7370/40-2 Adaptor

for use with insert tools with a lateral dovetail profile in torque wrenches with 14 x 18 mm internal square drives. Caution! Modified settings on torque wrench (refer to note on p. 197).



| Code | mm | b mm | h mm | S mm | Δg |
|-------------|-------|------|------|------|-----|
| 58 29 00 42 | 14x18 | 31.5 | 9.5 | 34.6 | 138 |

1821 Tool holder

with tool carrier to receive insert/shell tools (without torque function).



| Code | mm | L mm | Δg |
|-------------|-------|------|-----|
| 18 21 00 01 | 14x18 | 575 | 720 |