

↔		↔		⊥		⌒		⌒		⊞	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
8	5/16	14	0,55	50	730	64	2,50		0,135	0,090	
10	3/8	16	0,63	50	730	80	3,00		0,160	0,110	
13	1/2	20	0,79	40	600	104	4,00		0,225	0,150	
16	5/8	24	0,94	40	600	128	5,00		0,320	0,215	
19	3/4	27	1,06	40	600	152	6,00		0,370	0,250	
25	1	34	1,34	40	600	200	8,00		0,525	0,355	
NA		LA		NEU		EMEA		SA		AP AU	



591AE

Crop spraying 40 bar (600 psi) - PVC

Tube: Black PVC
Reinforcement: High tensile textile cords
Cover: Blue PVC - abrasion and ozone resistant.
Use: Crop spraying of fertilizers, pesticides and weed-killers
Safety factor: ≤10 mm and 25 mm 2,5:1 >10 mm 3:1
Temperature: -5 °C +60 °C (+23 °F +140 °F)

↔		↔		⊥		⌒		⌒		⊞	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
8	5/16	15	0,59	80	1200	64	2,50		0,160	0,110	
10	3/8	18	0,71	80	1200	80	3,00		0,230	0,155	
13	1/2	22	0,87	80	1200	104	4,00		0,320	0,215	
NA		LA		NEU		EMEA		SA		AP AU	



593AK

Crop spraying 80 bar (1200 psi) - PVC

Tube: Black PVC
Reinforcement: High tensile textile cords
Cover: Yellow ribbed PVC with longitudinal black stripe - abrasion and ozone resistant.
Use: Crop spraying of fertilizers, pesticides and weed-killers
Safety factor: 2,5:1
Temperature: -5 °C +60 °C (+23 °F +140 °F)

↔		↔		⊥		⌒		⌒		⊞	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
25	1			8	120	113	4,50	70	0,290	0,195	
32	1 1/4			7	100	144	5,75	70	0,390	0,265	
38	1 1/2			6	90	171	6,75	70	0,510	0,345	
45	1 3/4			6	90	203	8,00	70	0,670	0,455	
51	2			5	75	230	9,00	70	0,760	0,515	
63	2 1/2			5	75	284	11,25	70	1,180	0,795	
76	3			5	75	342	13,50	70	1,510	1,015	
NA		LA		NEU		EMEA		SA		AP AU	



2660A

Air seeder - PVC

Construction: Transparent PVC - abrasion and ozone resistant
Reinforcement: Black shock resistant rigid PVC
Use: Agricultural seed transfer in "Air-Flo" seeding equipments
Safety factor: 3:1
Temperature: -5 °C +60 °C (+23 °F +140 °F)

↔		↔		⊥		⌒		⌒		⊞	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
32	1 1/4	42	1,65	10	150	128	5,00	100	0,870	0,585	
38	1 1/2	48	1,89	10	150	152	6,00	100	1,020	0,690	
45	1 3/4	55	2,17	10	150	180	7,00	100	1,190	0,800	
51	2	61	2,40	10	150	204	8,00	100	1,320	0,890	
63	2 1/2	75	2,95	10	150	252	10,00	90	2,050	1,380	
76	3	88	3,46	10	150	304	12,00	90	2,460	1,655	
NA		LA		NEU		EMEA		SA		AP AU	



702AA

Air seeder

Tube: Black conductive NR
Reinforcement: High tensile textile cords with embedded steel helix wire
Cover: Black NBR/PVC - oil, heat, abrasion and ozone resistant
Use: Agricultural seed transfer in "Air-Flo" seeding equipments
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)