

↔		↔		⌚		⤴		⚡		♻️	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
12	15/32	22	0,87	50	750	84	3,25		0,325	0,220	
NA	LA	NEU		EMEA	SA	AP	AU				



395BT
Hot water wash down 50 bar (750 psi)
EU 10/2011 A+B+C

Tube: Grey non-toxic PVC
Reinforcement: High tensile textile cords
Cover: Light blue synthetic elastomer - abrasion, ozone and oil resistant
Use: Hot water wash down.
 Specially designed for the food and dairy industry.
 Designed for 50 bar at 70° C continuous use. Food grade
Safety factor: 3:1
Temperature: -10 °C +70 °C (+14 °F +158 °F)

↔		↔		⌚		⤴		⚡		♻️	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
19	3/4	31	1,22	10	150				0,640	0,435	
25	1	37	1,46	10	150				0,790	0,535	
32	1 1/4	46	1,81	10	150				1,150	0,775	
38	1 1/2	52	2,05	10	150				1,350	0,910	
NA	LA	NEU	EMEA	SA	AP	AU					



351LL
Hot water wash down 10 bar (150 psi)
built in nozzle

Tube: White EPDM
Reinforcement: High tensile textile cords
Cover: White EPDM - heat, abrasion and ozone resistant
Use: Hot and cold water wash down in paper mills and the food industry where a built in rubber nozzle is required to avoid floor and equipment damage
Safety factor: 4:1
Temperature: -40 °C +120 °C (-40 °F +248 °F)

↔		↔		⌚		⤴		⚡		♻️	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
19	3/4	31	1,22	10	150				0,610	0,410	
25	1	37	1,46	10	150				0,750	0,505	
32	1 1/4	46	1,81	10	150				1,110	0,750	
38	1 1/2	52	2,05	10	150				1,300	0,875	
NA	LA	NEU	EMEA	SA	AP	AU					



351LG
Hot water wash down 10 bar (150 psi)
built in nozzle

Tube: White EPDM
Reinforcement: High tensile textile cords
Cover: Green EPDM - heat, abrasion and ozone resistant
Use: Hot and cold water wash down in paper mills and the food industry where a built in rubber nozzle is required to avoid floor and equipment damage
Safety factor: 4:1
Temperature: -40 °C +120 °C (-40 °F +248 °F)