

**THERMOPLASTIC HOSE**
**R8X**

FIBRE BRAID THERMOPLASTIC HOSE

BRAIDED FIBRE REINFORCED SLIMLINE HOSE - SAE

100R8



Part Number	Internal Size	Internal DN	Internal Diameter - inches	External Diameter - inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min. bend radius - inches	Min bend radius - mm
2R8X	02	4	1/8	0.32	8	6000	420	24000	1680	1	25
3R8X	03	5	3/16	0.35	8.9	5000	350	20000	1400	1.2	30
4R8X	04	6	1/4	0.45	11.5	5000	350	20000	1400	2	50
5R8X	05	8	5/16	0.53	13.4	4300	300	17200	1200	2.2	55
6R8X	06	10	3/8	0.61	15.5	4000	280	16000	1120	2.4	60
8R8X	08	12	1/2	0.78	19.9	3500	245	14000	980	3.2	80
10R8X	10	16	5/8	0.92	23.4	2900	200	11600	800	4.9	125
12R8X	12	19	3/4	1.06	26.9	2300	165	9200	660	6	150

† - Please contact Hydraulink for further details and availability.

Pricing current as at 14 Feb 2017 and excludes GST. Hydraulink reserve the right to change pricing and technical specifications without notice.