



GENERAL INFO

MAXIPLUS™ STAINLESS STEEL HOUSINGS

The Puretec SS MaxiPlus™ are ideal for large scale commercial and industrial applications.

The Puretec SS MaxiPlus™ Series housings are suitable for the most demanding applications such as high pressure, temperature or corrosive, harsh conditions. The housings are capable of temperatures up to 99°C at 2,070 kPa and a maximum flow of 180 litres per minute.

MATERIALS OF CONSTRUCTION

- Material: 304 stainless steel
- Standard: NPT/ BSP thread
- Filter Cartridge: Double open end Cartridges of any kind
- O-Ring: Buna-N
- Maximum Temperature: 99°C
- Maximum Pressure: 2,070 kPa
- Application: Suitable for industry and other relative water treatment

FEATURES & BENEFITS

- Large diameter for high flow rates
- High capacity stainless steel filter housings
- High pressure and temperature applications
- Suitable for harsh and corrosive conditions
- Polished 304 stainless steel construction
- Heavy duty units for large scale commercial/industrial applications

HOUSING SPECIFICATIONS AND PERFORMANCE DATA

Model	Description	Housing Size (inches)	Connection Size	Max. Flow (Lpm)
SS25MP1	304 Stainless steel head and housing	10"	1"	90
SS40MP2	304 Stainless steel head and housing	20"	1½"	180

Each housing includes a spanner tool, a mounting bracket kit and drain plug