

# CRETE-SHIELD

**CRETE-SHIELD** is formulated with surfactant and chemicals to prevent concrete and other foreign materials adhering to equipment.

**CRETE-SHIELD** can be used to prevent cement, concrete, mortar, grout and stucco from sticking to treated surfaces.

It is especially useful to protect concrete build up on ready-mix trucks, cement mixers, vehicles, forms, molds, cement buggies, pumps, trowels, screeds, concrete saws, augers or any other surface.

## Key Features

- Easy to use and helps keep your equipment looking new. It even removes the oxidation from paint and returns the paint to its original luster.
- 100% biodegradable, non toxic, non flammable, non corrosive, non fuming and will not harm paint, metals, glass or other surfaces.



## Directions For Use

- Apply **CRETE-SHIELD** on surface to be protected with a sponge mop, wool applicator or sprayer. Allow to dry for a minimum of 30 minutes. Surface will turn shiny upon **CRETE-SHIELD** drying as it hardens. After the surface dries, **CRETE-SHIELD** will help impede concrete from bonding to treated surfaces.
- **CRETE-SHIELD** can be reapplied over existing protected surfaces once cleaned. To remove **CRETE-SHIELD**, wash covered area with a High-Alkaline- Detergent (e.g.Truck wash), rinse with high-pressure-washer or hose.
- **CRETE-SHIELD** works best between 10°C and 35°C.
- DO NOT WET SURFACE before applying **CRETE-SHIELD**, apply to dry surface for best results. Please refer to SDS (Safety Data Sheet) and product labelling instructions provided on this product for other information.

CODE: 1114 - 750ML

CODE: 1117 - 5LTR

CODE: 1115 - 20LTR

